Assembly Instructions
Aimee Chandelier # HAME0855

WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. READ AND SAVE THIS INSTRUCTION.

1. Attach nipple(-a) to the mounting strap, then secure it with a washer and hex nut.
2. Attach the mounting strap to the outlet box by using two mounting screws.
3. Carefully thread the wires through the upper fixture and loop, screw the upper fixture onto nipple(-c) securely.
4. Secure the loop onto nipple(-b).
5. Adjust the arms of the fixture according to the drawing of the package.
   Important:
   a. The arms should be positioned with equal distances between them.
   b. The arms should be fixed securely.
6. Choose the length of the chain you need, then weave the fixture wire and the fixture grounding wire through the chain. Then connect one end of the chain with the loop by using the loop lock.
7. Secure the top loop to nipple(-a) tightly.
8. Thread the fixture wire and fixture grounding wire through the collar, canopy, top loop, nipple(-a) and mounting strap.
9. Connect the other end of the chain with the top loop by using the loop lock.
10. Pull out the outlet wires and house grounding wire from the outlet box. Make wire connections with wire nuts:
    ---The smooth wire (marked) from the fixture to the black wire from the power source.
    ---The ridged wire (unmarked) from the fixture to the white wire from the power source.
    ---Attach the fixture grounding wire to the mounting strap with the green grounding screw. Then connect it to the house grounding wire with the wire nut.
    Carefully put the wires back into the outlet box.
11. Attach the canopy to the mounting strap by inserting the top loop, then secure it with the collar.
12. Attach a rubber pad, glass holder and decorative cap to the holder by inserting nipple(-d), then secure them with the finial.
13. Attach the candle covers and glass caps onto the sockets, then install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.
14. Install the crystal drops and pearl strands as shown in diagram.
    Note: To replace broken crystal drops -Open the pins to remove the crystal drops, hook the new crystal drops, and then close back pins. Avoid bending the pins into sharp angle.
15. Turn on the power at the main fuse or circuit breaker box.

Note: Spare crystal drops are enclosed in hardware bag.	 ① (3) PCS.	 ② (3) PCS.	 ③ (15) PCS.